

## DUPLI-COLOR Blackboard paint

## Technical Information



DUPLI-COLOR BLACKBOARD PAINT is a special effect brush paint. With this lacquer you create a surface, which you can write on with chalk. For application on smooth indoor surfaces, e.g. walls, doors, furniture etc. – not magnetic.

**Ord.-no:** 368103, 368110, 446429, 446436

### Quality & properties

- High-quality acrylate dispersion
- Quick-drying
- Water-soluble
- Environmental-friendly due to waterbased formulation
- Less bad odour
- Washable
- Good coverage
- Ease of handling

### Physical & chemical data

- Base: acrylate dispersion
- Colourname:
  - black
  - green
- Degree of gloss: mat GU
- Efficiency: 375 ML – 3 m<sup>2</sup>
- Dry to touch: 2 h
- Dust dry: 2 h
- Overcoatable: 12 h
- Surfaces: wood, metal, paintable plastics, smooth wallpapers, masonry, finery, concrete
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 5 y
- Content:
  - 375 ML
  - 750 ML

### How to use

Make the surface free from loose flakes of old paintings, rust and fat.  
Apply putty to fill small cracks.  
The surface should be as smooth as possible, absolutely dry and clean.  
Carefully mask areas you want to protect from paint splatters.  
By applying a suitable primer you can improve the adhesion of the paint.  
Prepare paintable plastics with a Plastic Primer.  
Before application, carefully stir up the paint  
Temperature of the object and surrounding temperature should be at least +7°C.  
Apply with a brush or a roller.  
For the basic coat thin the blackboard paint down with 5 ml of water to 100 ml lacquer (5 %).  
For the 2nd layer (final coat) apply the unthinned blackboard paint.  
After each coating: when the surface is dry, slightly sand and remove the abrasive dust.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 21, 2025** – This release replaces all eventually earlier issued versions.