

## DUPLI-COLOR PRIMER AUTOMOTIVE

## Technical Information



The ideal primer for use as filler and as an adhesion promoter between surface and final coat. Coatable with air-drying acrylic-, synthetic and nitro-combi lacquers. For metal, wood, ceramics, stone, carton and others. The ideal primer for the subsequent coating with DUPLI-COLOR Auto-Spray.

**Ord.-no:** 189807, 132636, 191268, 133336, 191510, 132711, 191282

### Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Grants the economical application of the top coat
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Very good flow, smooth surface
- Especially user-friendly due to durable quality, which is easy to apply and easy to sand and re-coat
- For indoor and outdoor applications

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - grey
  - red
  - white
- Smell: Characteristic
- Degree of gloss value: mat, 10 ±2
- Efficiency:
  - 12 ML – small spots m<sup>2</sup>
  - 150 ML – small spots m<sup>2</sup>
  - 400 ML – small spots m<sup>2</sup>
- Dust dry: 10 min
- Dry to touch: 30 min
- Completely dry: 24 h
- Overcoatable: 30 min
- Surfaces: metal, wood, ceramics, stone, carton and others
- Minimum Working Temperature:
  - 10 °C
  - 10
- Maximum Working Temperature:
  - 25 °C
  - 25
- Flash point:
  - 27
  - n.a.
- Storage stability: 10 years
- Content:
  - 12 ML
  - 150 ML
  - 400 ML

---

**How to use**

De-rust, sand and clean the surfaces to be painted.  
Apply putty, if necessary.  
The surface has to be clean, dry and free from rust and fat.  
Shake cans for 2 minutes.  
Test spray at an invisible spot.  
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.  
Spray from a distance of approx. 25 cm.  
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.  
Afterwards apply the top coat.  
Coatable with synthetic or acrylic lacquers.  
Do not spray over synthetic lacquers!

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of July 10, 2025** – This release replaces all eventually earlier issued versions.