

DUPLI-COLOR PRIMER AUTOMOTIVE

Technical Information



The ideal primer for use as filler and as an adhesion promoter between surface and final coat. Coatable with air-drying acrylic-, synthetic and nitro-combi lacquers. For metal, wood, ceramics, stone, carton and others. The ideal primer for the subsequent coating with DUPLI-COLOR Auto-Spray.

Ord.-no: 189807, 132636, 191268, 133336, 191510, 132711, 191282

Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Grants the economical application of the top coat
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Very good flow, smooth surface
- Especially user-friendly due to durable quality, which is easy to apply and easy to sand and re-coat
- For indoor and outdoor applications

Physical & chemical data

Base: Nitrocombi resin

Colourname:

- grey
- red
- white

Degree of gloss: mat GU

Efficiency:

- 12 ML – small spots m²
- 150 ML – 0.3 m²
- 400 ML – 0.8 m²

Dry to touch: 30 min

Dust dry: 10 min

Completely dry: 24 h

Overcoatable: 30 min

Surfaces: metal, wood, ceramics, stone, carton and others

Minimum Working Temperature:

- 10 °C
- 10

Maximum Working Temperature:

- 25 °C
- 25

Flash point:

- 27
- n.a.

Storage stability: 10 y

Content:

- 12 ML
- 150 ML
- 400 ML

How to use

De-rust, sand and clean the surfaces to be painted.
Apply putty, if necessary.
The surface has to be clean, dry and free from rust and fat.
Shake cans for 2 minutes.
Test spray at an invisible spot.
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.
Spray from a distance of approx. 25 cm.
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.
Afterwards apply the top coat.
Coatable with synthetic or acrylic lacquers.
Do not spray over synthetic lacquers!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.