

DUPLI-COLOR profi Insulation Primer

Technical Information



Fast drying insulating primer spray for interior and exterior application on the basis of synthetic resins, with excellent isolation and barrier effect against many different types of stains (especially water stains) on mineral-based substrates (plaster etc.), wood and concrete. Can be painted over with all emulsion paints, alkyd-based, water-based and acrylic paints; not with two-component paints. Adjustable spray cone width (horizontally and vertically)

Ord.-no: 478413

Quality & properties

Excellent insulation and protection against many types of stains such as water stains on mineral surfaces (plaster, etc.), timber and concrete
 Quick and easy to apply
 Can be recoated with all paints, alkyd- and water-based acrylic coatings
 Based on synthetic resins
 Adjustable spray cone width

Physical & chemical data

Base: Special resin
 Colourname: white
 Smell: Characteristic
 Efficiency: 400 ML – 1.0 - 1.5 m²
 Dust dry: 6 min
 Dry to touch: 60 min
 Overcoatable: 60 min
 Surfaces: Wood, metal and on mineral substrates like concrete, stone, plastering etc.
 Minimum Working Temperature: 10 °C
 Maximum Working Temperature: 25 °C
 Storage stability: 10 years
 Content: 400 ML

How to use

Clean surfaces to be painted thoroughly with DUPLI-COLOR Degreaser art.no. 478376, then sand
 The area must be dry and free of dust and grease
 Shake can well for 3 minutes
 Carry out spray test
 2-3 coats

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.